

Walls and Ceilings



03/2014

NIROPLAST

Product Description

A washable matt acrylic paint for interior walls. Particularly indicated for painting gypsum board and gypsum plaster. Also suitable for painting new wall surfaces after a proper surface preparation and application directly on existing paint. The paint has a good opacity and spread rate, is easy to apply and does not yellow.

Surface Preparation

thoroughly prepare the surface to obtain good results. **Gypsum board:** Treat the joints between gypsum boards using Gold Bond Joint Compound and embedding tape, after drying sand to obtain a smooth surface. Remove dust, apply Primer S and wait until dry. **Gypsum plaster:** sand slightly to obtain a smooth homogeneous surface and clean from dust. **Old surfaces:** Clean the surface from any foreign matter such as old whitewash, dust, peeling paint, grease etc. Make sure that the existing paint is firmly attached to the surface. Remove unattached paint particles with a scratcher and sand paper. When required, repair the surface with Maximo Crack Filler or Gold Bond, sand and apply Primer S.

Application

Stir the paint well before use. Apply the paint in 2 coats by a roller or sprayer within 6 and 24 hours after the application of a primer. Let dry at least 2 hours between coats.

Clean-up

Soap and water.

Finish

Finish: Matt
Color: White.

Technical Data

Theoretical Coverage*: 9 m²/L per coat.

Dilution: Mix for the first time without dilution. Dilute further with up to 20 % for the first coat and up to 10 % for additional coats.

Dry-Time

To touch: 1 hour.
To recoat: 4 hours.
Full cure: 24 hours.

Shelf Life

18 months in a cool, dry place.

Packaging

5, 18 liters.

Health and Safety precautions: The material does not contain lead. During application it is advisable to wear goggles and ensure that the site is adequately ventilated. If the paint comes in contact with eyes, rinse well under running water and seek medical assistance. Keep the package tightly closed. Do not hang on the handle. Keep away from children. Do not mix materials not recommended by Nirlat.

* The practical coverage depends on a variety of factors such as type of surface, application method, paint shade, background color, the professionalism of the applicator as well as weather conditions. It is accepted to assume that it amounts 75 % of the theoretical coverage.

