

Wall Preparation



11/2015

BONDING PRIMER



Product Description

Water-based white acrylic primer for interior and exterior walls intended to fix the surface and improve its bonding with acrylic paints and plasters. Penetrates the surface and strengthens it. Reduces the absorption of the surface, which enables obtaining a more homogeneous topcoat with a better spread rate.

Surface Preparation

Clean new black plaster with a broom and rinse with water to remove loose grains of plaster. On existing walls remove all peeling or loose paint and ensure that the remaining paint is firmly attached to the walls. Repair defects and holes and smooth with Maximo Crack Filler or Altek Violet (with addition of 25% cement). Open cracks and, after primer is applied, fill with Niroseal or Flexible Wall Putty. Wash painted walls with a water pressure machine to remove soot, dust and dirt.

Application

Roller, brush or sprayer. Use a brush in corners where the roller cannot reach. Do not apply the material when the temperature is below 7 °C or when rain is predicted.

Clean-up

Clean tools and hands with water immediately after use.

Finish

Finish: Matt

Color: White, can be tinted in pastel shades.

Technical Data

Theoretical Coverage: 3.9 m²/L on black plaster and 5.5 m²/L on spackle plaster.

Dry-Time

To touch: 4-6 hours.

Between coats: 4-6 hours.

Final drying: 24 hours.

Shelf Life

18 months in a cool dry area in a closed container. Protect from freezing.

Packaging

5, 18 liters.

Health and Safety precautions: The material does not contain lead. During application it is advisable to wear goggles and ensure that the site is adequately ventilated. If the paint comes in contact with eyes, rinse well under running water and seek medical assistance. Keep the package tightly closed. Do not hang on the handle. Keep away from children. Do not mix materials not recommended by Nirlat.

General Notes: The recommendations are not to be perceived as substitute for consultation in writing specific work specifications. All the data and recommendations presented here are based on tests, knowledge and experience that have accumulated in the laboratory and on-site and they are highly reliable. This is not to be interpreted as a general warranty either explicit or implicit. The warranty is for product quality only. The user must examine the suitability thereof for his purposes. We reserve the right to update or change the data without prior notice.

