

11/2016

## FLEXIBLE WALL PUTTY

### Product Description

Flexible wall putty for filling cracks in exterior walls in order to prevent them from reappearing.

### Surface Preparation

Open cracks that aren't hairline cracks with the aid of a mortar or screwdriver, along the length of the crack. Rinse the building's walls with a high-pressure water machine to remove dust and dirt while the cracks are open.

### Application

Suitable for filling in cracks in exterior walls after they have been opened. Apply a coat of white Primer X on the sides of the crack in order to permit full adhesion of the putty inside the crack. Fill the crack with Flexible Wall Putty with the aid of a mortar and smooth with a wet brush in order to smooth it flush with the surface. In the case of cracks that don't have to be opened, apply the Flexible Wall Putty with the aid of a brush along the entire length of the crack plus 2-3 cm on either side.

### Clean-up

Tools can be cleaned with soap and water immediately after use.

### Finish

**Finish:** Matt.

**Color:** White.

### Technical Data

**Theoretical Coverage:** according to the depth of the area being filled.

**Limitations:** Do not apply the material when the temperature is below 7°C or when rain is predicted.

### Dry-Time

**To recoat:** 1-2 hours.

**To touch:** 1 hour.

**Final drying:** 24 hours.

### Shelf Life

24 months in a cool dry area in a closed container. Protect from freezing.

### Packaging

6 Kilogram.

**Health and Safety precautions:** The material does not contain lead. During application it is advisable to wear goggles and ensure that the site is adequately ventilated. If the paint comes in contact with eyes, rinse well under running water and seek medical assistance. Keep the package tightly closed. Do not hang on the handle. Keep away from children. Do not mix materials not recommended by Nirlat.

**General Notes:** The recommendations are not to be perceived as substitute for consultation in writing specific work specifications. All the data and recommendations presented here are based on tests, knowledge and experience that have accumulated in the laboratory and on-site and they are highly reliable. This is not to be interpreted as a general warranty either explicit or implicit. The warranty is for product quality only. The user must examine the suitability thereof for his purposes. We reserve the right to update or change the data without prior notice.