

11/2017

UNIOR

Product Description

Synthetic satin enamel based on single component polyurethane resin and intended for interior and exterior painting of wood, metal and walls. The material is easy to use, does not drip and has excellent flow and leveling properties. Unior is highly durable in exterior and interior use, resistant to wash, scratches and abrasion.

Surface Preparation

Clean the surface from dirt, dust, grease or any other foreign material. Make sure that the existing paint is firmly attached to the surface. Sand to remove gloss and eliminate the peeling particles of old paint with a sand paper. Remove grease and rust and apply a suitable primer.

Galvanized metal and aluminum: Apply "Phenolic 503 Primer".

Black metal: Apply "Antirust" or "Phenolic 503 Primer". When painting on existing paint in good condition, sand the surface and apply "Unior" directly.

Wood Surfaces: When painting on new wood, apply "Oil for Deck". Await full drying and when needed smooth by "Wood Filler". Sand until obtaining smooth surface and apply a coat of "Synthetic First Coat".

Walls: Sand the wall surface and smooth where needed with "Altek Violet". Apply a coat of "Primer X".

Application

Brush, roller or a sprayer in 2 coats. Stir well before application.

Clean-up

Tools can be cleaned with white spirit immediately after use.

Finish

Finish: Satin.

Color: White +1500 shades of the Nirlat colour deck + RAL shades.

Technical Data

Theoretical Coverage*: 10 m²/L in single coat or 5.00 m²/L in 2 coats.

Dilution: Brush: 10 % white spirit; sprayer: 20 % of Thinner 032 (Xylene)

Dry-Time

To touch: 2-3 hours.

Final drying: 24 hours.

Shelf Life

24 months in a cool dry area in a closed container. Protect from freezing.

Packaging

0,25, 0,75, 2,5, 4,5 liters.

Health and Safety precautions: The material does not contain lead. During application it is advisable to wear goggles and ensure that the site is adequately ventilated. If the paint comes in contact with eyes, rinse well under running water and seek medical assistance. Keep the package tightly closed. Do not hang on the handle. Keep away from children. Do not mix materials not recommended by Nirlat.

* The practical coverage depends on a variety of factors such as type of surface, application method, paint shade, background color, the professionalism of the applicator as well as weather conditions. It is accepted to assume that it amounts 75 % of the theoretical coverage.