



02/2011

MICRO PRIMER

Product Description

Rough and granulated primer with addition of quartz sand intended for improving the bonding between smooth, little absorbing surfaces and the plaster. Can be applied on smooth wall surfaces such as smooth concrete, plaster board, plaster, cement board and wall paint. Micro primer adheres to the surface, strengthens it and creates a much rougher texture enabling a much better mechanical bonding of further plaster coat.

Surface Preparation

Clean the surface to remove dust, dirt or lose paint and to obtain a stable infrastructure. For old exterior walls rinse the wall surface by high pressure water machine at least 150 atmospheres and wait until the surface is completely dry.

Application

The product is ready to use. Apply with a roller, brush or a sprayer. Wait at least 6 hours before applying a further coat. Ensure complete coverage of the surface.

Clean-up

Tools can be cleaned with soap and water after use.

Finish

Finish: Matt. **Color:** Grainy brown.

Technical Data

Theoretical Coverage: 4 m2/L.

Limitations: Do not apply when the temperature is below 5^oC or when rain is expected.

Dry-Time

Final drying: 24 hours.

Shelf Life

24 months in a cool dry area in a closed container. Protect from freezing.

Packaging

1, 7, 21 Kilograms.

Health and Safety precautions: The material does not contain lead. During application it is advisable to wear goggles and ensure that the site is adequately ventilated. If the paint comes in contact with eyes, rinse well under running water and seek medical assistance. Keep the package tightly closed. Do not hang on the handle. Keep away from children. Do not mix materials not recommended by Nildst

General Notes: The recommendations are not to be perceived as substitute for consultation in writing specific wok specifications. All the data and recommendations presented here are based on tests, knowledge and experience that have accumulated in the laboratory and on-site and they are highly reliable. This is not to interpreted as a general warranty either explicit or implicit. The warranty is for product quality only. The user must examine the suitability thereof for his purposes. We reserve the right to update or change the data without prior notice.

THE STANDARDS INSTITUTION OF I

